

INNOVATION. COMMITMENT. EXCELLENCE

IRP-100+

FAST EFFICIENT AFFORDABLE

Whether you're running a small boutique, a bustling cafe, or a fast-paced retail shop, IRP-100+ is your go-to solution for affordable and reliable POS receipt printing.



Features

3-in1 interface, 200-250mm/s print peed

Allow print density and speed to be fine-tuned

Multifunctional button and status indicator available

New utility to view print length, number of cuts and more

Allow users to upgrade printer firmware



Technical Specifications

Specification

Print Method	Direct thermal
Print Speed	200~250mm/s
Paper Width	79.5±0.5mm
Print Width	64/72mm
Interface	Serial+USB+Ethernet
Reliability(Mechanism)	150km
Weight	1.05KG
Dimension	185×130×130mm(W×D×H)
Columns	Font A - 42columns or 48columns / Font B - 56columns or 64columns /
	Simplified/Traditional Chinese - 21columns or 24columns
Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots
	Simplified/Traditional Chinese: 24×24dots
Code page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/
	Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII /Latvian/
	Arabic/PT151,1251/PC737/WPC1257/Thai Vietnam/PC864/PC1001/
	(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/
	CODE93/CODE128/QRCODE
Data	128K bytes
NV Flash	256K bytes
Cash drawer out	DC 24V/1A
Power adaptor	Input: AC 110V/220V, 50~60Hz Output: DC 24V/2.5A
Work environment	Temperature: $0\sim45^{\circ}\mathrm{C}$, Humidity: $10\sim80\%$
Storage environment	Temperature: -10 $^{\circ}$ 60 $^{\circ}$ C, Humidity: 10 $^{\circ}$ 90%