



INNOVATION. COMMITMENT. EXCELLENCE



IS-2220



Features

- Plug and play and easy to setup
- Can interpret variety of 1D & 2D code
- Durable and reliable



Technical Specifications

Specification

Performance Parameters

Light Sources:	617nm LED Aimer, White LED
Supported Symbologies:	1D: Codabar, Code 11, Code 93, EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Interleave 2 of 5, Matrix 2 of 5, MSI Code, Industrial 2 of 5, GS1-DataBar. 2D: QR Code, Data Matrix, PDF417.
Scan Type:	Image CMOS
Precision:	≥ 5mil
Scan Mode:	Manual/Continuous/Automatic Scintillation
Scan Angle:	Yaw65°, Rotaion 30°, Pitch60°
Depth of scan field:	60-250mm
Error Rate:	Less than 1/5million
Interface:	USB-HID, RS232

Physical Parameters

Dimensions:	79.7mm*69mm*155mm
Weight:	113.4g
Material:	ABS+PC
Cable Length:	2M

Environmental Parameters

Operating Temperature:	-20 ~60
Storage Temperature:	-40 ~70
Relative Humidity:	5%~95% (Non-condensing)
Drop/Shock Resistance:	Withstands multiple times 1.5 meters drops to concrete

Electrical Parameters

Voltage:	DC5V±5%
Operating Current:	135mA

