

ice POSsibly the BEST!

INNOVATION. COMMITMENT. EXCELLENCE



BLUETOOTH IS-2225



Features

- Plug and play and simple setup
- Can interpret variety of 1D & 2D code
- Directly paired use with mobile phone / tablet / laptop with bluetooth function
- Transmission distance of 30-50 meter via wireless bluetooth
- Touch charging base



Specification

Performance Parameters

Light Sources:	617nm LED Aimer, White LED
Supported Symbologies:	1D: EAN13, EAN8, UPC-A, UPC-E0, UPC-E1, Code 128, Code 39, Code 93, CodaBar, Interleave 2 of 5, Industrial 25, Matrix 2 of 5, Code11, MSI-Plessey, RSS-14, Limited RSS, Extended RSS 2D: QR Code, Data Matrix(ECC200), PDF417
Scan Type:	Image CMOS
Scan Mode:	Manual/Continuous/Automatic Scintillation
Scan Angle:	Yaw65°, Rotaion 30°, Pitch60°
Precision:	1D≥ 5mil, 2D≥ 10mil
Depth of scan field:	35-190mm(EAN13, 13mil, PCS90%)
Error Rate:	1/5million
Interface:	USB-HID
Communication mode:	Paired dedicated receiver: 2.4g communication; Paired mobile bluetooth devices: bluetooth BLE4.0
Transmission distance:	30-50M(Open Yard)
Storage Mode:	Offline Storage Mode: When the scanner exits the connection range, the data is automatically stored. Storage capacity is 512000 characters. Inventory storage mode: Scanner can enter inventory mode, storage capacity is 512000 characters.
Pairing Mode:	One to One: One Scanning Gun Pairs One Receiver, One scanner paired with a Bluetooth mobile device.

Environmental Parameters

Operating Temperature:	-20 ~60
Storage Temperature:	-40 ~70
Relative Humidity:	5%~95% (Non-condensing)
Drop/Shock Resistance:	Withstands multiple times 3 meters drops to concrete

Physical Parameters

Dimensions:	86.6mm*137mm*169mm
Weight:	113.4g
Cable Length:	0.8M
Material:	ABS+PC

Electrical Parameters

Voltage:	DC5V±5%	Battery Working Time:	6h
Operating Current:	280mA	Lithium battery:	1400mA
Standby Current:	0mA(Standby is to cut off battery power)	Charging Time:	3.5h
Charging Mode:	Contact the charging		

